

SURE SEAL® GRAFFITI SHIELD TECHNICAL DATA

Product Description:

This product is a superior water-based graffiti shield for all masonry surfaces as well as painted exterior walls, porcelain, ceramic, metals, and concrete. It is invisible upon application, environmentally friendly, non-toxic, non-flammable and UV light resistant. It provides a tough surface barrier against the effects of paint and permanent markers. There are no discoloration or demarcation lines when Sure Seal® Graffiti Shield is used. Once applied and allowed to cure, Sure Seal® Graffiti Shield leaves a durable, protective finish lasting a minimum of five (5) years on vertical surfaces.

Mixing:

Product is ready to use. Shake before using. Do not dilute.

Preparing the Surface:

All surfaces must be clean and free from debris. Always test product in an inconspicuous area for suitability.

Directions for Application:

Begin application at the highest point of the surface to be treated. Completely wet the surface by applying Sure Seal® Graffiti Shield with a lambswool applicator, paint brush, roller, pump spray or airless sprayer at 60 PSI or less. When treating rough surfaces a pump or airless sprayer is recommended. Apply one coat evenly, thoroughly saturating the surface being treated. Allow at least two hours drying time, then apply a second coat. Product will perform when dry, but for optimum protection, surface should be allowed 24 hours curing time.

Maintenance:

There is no need to use harsh cleaning agents such as abrasive powders, ammonia, acids, bleach, solvents or severe scrubbing pads. To remove graffiti from large treated areas, use of a power washer up to 1000-1500 PSI (depending upon the surface) should be used, preferably with hot water. For small areas, inside areas, or areas where the use of a power washer is not practical, clean with Sure Seal® Graffiti Remover and rinse well with water. Allow surfaces to dry. [See also: %Procedure For Removal of Graffiti on Surfaces Protected with Sure Seal® Graffiti Shield+located in this manual for further information.]

Coverage:

One litre will cover approximately 8-40 sq. metres depending upon the porosity of the surface to be treated and method of application.

Quantities:

Supplied in 20 litre or 200 litre drums.

First Aid:

Eye Contact: If in eyes, immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention.

Skin: Prevent prolonged contact with skin. Wash area with soap and water.

Ingestion: If swallowed DO NOT induce vomiting. Wash out mouth with water and give plenty of water to drink. Seek medical attention. Never give anything by mouth to an unconscious person.

Inhaled: No first aid measures normally required. If vapours or mists inhaled and irritation develops, remove to fresh air and observe until recovered. If irritation becomes painful or persist more than about 30 minutes, seek medical advice.

Protective Clothing: Wear appropriate chemical resistant protective clothing to prevent skin contact. The use of a dust or vapour mask is suggested when airborne exposure is likely, especially if in confined or dusty spaces. Consult AS/NZS 1715 in selecting suitable equipment.

Handling and Storage:

Keep tightly closed and store in original container. Once contents are opened, excellent storage stability of six months minimum under normal conditions. Maintain a high level of personal hygiene when using this product. Wash your hands before eating, drinking, smoking or using the toilet.

Transport Information:

Proper shipping name: None Allocated
Not Regulated

(This product has no UN classification. Not a Scheduled Poison. Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (6th Edition).)

See Material Safety Data Sheet for complete warnings and safe handling instructions.

KEEP OUT OF REACH OF CHILDREN